

Built Stronger to Last Longer
Gooseneck
Trailer Mfg. Co., Inc.

Contractor HD
(Heavy Duty)



“Tough Jobs Demand A Tough Trailer”

The Gooseneck Contractor HD (Heavy Duty) is built to meet the rugged demands of the construction industry, while maintaining convenience and safety as a prime concern.

- Don't Settle For Less Than the Original Gooseneck Brand
- We Have Built Your Trailers For Over 40 Years

WWW.GOOSENECK.NET

sales@gooseneck.net
800-688-5490



4400 East Hwy 21, Bryan TX 77808
Box 832 Bryan, TX 77806-0832
979-778-0034 * Fax 979-778-0615

“Gooseneck Trailer Mfg. Co., Inc. reserves the right to change the design, features, options, materials, and/or specifications at any time, without notice, and without incurring any obligation for such changes. Contact Gooseneck Trailer Mfg Co., Inc. to determine what is offered at the time of your order.” Rev. 15.04.23
The GOOSENECK trademark is a registered trademark (U.S. Pat. & TM. Off. Number 1,857,615) and may only be used to describe genuine Gooseneck Trailers

Contractor HD

Standard Features

- 102" width
- 16' – 45' lengths
- straight deck
- 12" wide flange I-beam (19lbs. per FT.)
- 4" channel crossmembers on 2' centers
- 7" structural steel channel
- 3/16" formed neck gusset
- 10" and 12" steel channel neck
- adjustable 2-5/16" (25K) ball coupler (hitch)
- 2"x 8" tongue and groove treated floor; southern yellow pine
- sandblasted, primed with rust inhibitive primer, and painted with two coats of paint
- 1 spring loaded drop leg jack
- electric brakes (all axles)
- 235 85 R16 radial tires with 16" 8 hole wheels
- spare tire and rack
- heavy duty rub rails and stake pockets
- safety chains
- lights and brakes meet U.S.DOT required specifications
- conspicuity (reflective) tape
- sealed beam lights
- 24' and longer have torque tube
- 28' and longer have sway braces
- outriggers on 2' centers
- step with grab handle
- 5 year limited warranty

Optional Features

- extra bed length
- 4" drop axle
- adjustable 2-5/16" (30K) ball coupler (hitch)
- adjustable 3" (30K) ball coupler (hitch)
- adjustable king pin coupler (hitch)
- pintle hitch
- mini fifth wheel
- 6K, 7.2K, 8K, 10K, 12K, and 15K axles
- electric/hydraulic brakes
- 5' wood dovetail
- 5' self cleaning dovetail – angle iron
- 2 spring assisted flip ramps
- 3 spring assisted flip ramps
- 2 – 8' portable ramps
- 3 – 8' portable ramps
- 2 single speed jacks
- 2 drop leg jacks with 2 speed gear box
- 4' heavy duty neck deck
- 6' heavy duty neck deck
- rolling tail bar
- steel floor sandblasted, primed with rust inhibitive primer, and painted with two coats paint
- side binders with straps
- heavy duty "D" rings
- 24", 36" and 48" underbody toolbox
- expanded metal chain basket
- toolbox between uprights with lid
- 24", 36", and 48" stake/planks sides
- pipe bar
- 22lb. I-beam
- pierce beam
- load range G 14ply radial tires



WWW.GOOSENECK.NET

sales@gooseneck.net

800-688-5490

4400 East Hwy 21, Bryan TX 77808

Box 832 Bryan, TX 77806-0832

979-778-0034 * Fax 979-778-0615

"Gooseneck Trailer Mfg. Co., Inc. reserves the right to change the design, features, options, materials, and/or specifications at any time, without notice, and without incurring any obligation for such changes. Contact Gooseneck Trailer Mfg Co., Inc. to determine what is offered at the time of your order." Rev. 15.04.23
The GOOSENECK trademark is a registered trademark (U.S. Pat. & TM. Off. Number 1,857,615) and may only be used to describe genuine Gooseneck Trailers