

Built Stronger to Last Longer

Gooseneck

Trailer Mfg. Co., Inc.

5 Bale Haymaster



Our Haymaster trailer features a dual tilting mechanism that allows loading and unloading from either the left or the right. From feeding to hauling, we have you covered on both sides.

Features

Standard

- 32' bale end load (spear end of bale to load)
- 5 cradles (each cradle unloads both left and right with patented 2 sided dumping mechanisms)
- 8" channel iron neck with 3/16" formed neck gusset
- adjustable 2-5/16" (25K) ball coupler (hitch)
- 1 spring loaded drop leg jack
- electric brakes (both axles)
- 2 – 6K cambered spring axles with 1/4" wall thickness
- 8 hole 16" wheels
- 4 – 235 85 R16 radial tires
- spare tire rack only
- 5 tie down (ratchet) straps
- basket for strap storage
- safety chains
- lights meet U.S.DOT required specifications
- conspicuity (reflective) tape
- sandblasted, primed with rust inhibitive primer, and painted with 2 coats of paint
- 5 year limited warranty

Optional

- electric over hydraulic brakes
- 2 spring loaded drop leg jacks with two speed gear box
- spare tire wheel



WWW.GOOSENECK.NET

sales@gooseneck.net

800-688-5490

4400 East Hwy 21, Bryan TX 77808
Box 832 Bryan, TX 77806-0832
979-778-0034 * Fax 979-778-0615

"Gooseneck Trailer Mfg. Co., Inc. reserves the right to change the design, features, options, materials, and/or specifications at any time, without notice, and without incurring any obligation for such changes. Contact Gooseneck Trailer Mfg Co., Inc. to determine what is offered at the time of your order." Rev. 14.04.1
The GOOSENECK trademark is a registered trademark (U.S. Pat. & TM. Off. Number 1,857,615) and may only be used to describe genuine Gooseneck Trailers